

Delivering leading edge, innovative power solutions for more than **30** years....

Model:GT-21089-W

June 24, 2019

GT-21089-W

Information

Model Number GT-21089-W

Description GT-21089-W, ITE Power Supply, Wall Plug-in, Regulated Switchmode AC-DC Power Supply AC Adaptor, , Input Rating: 100-240V~, 50-60 Hz, , Output Rating: 19 Watts, Power rating with convection cooling (W) , 3.3-48V in 0.1V increments, Approvals:

Model Picture



Agency

Documents <http://www.globtek.info/certs/GT-21089/>

CE

EC-Declaration https://www.globtek.com/pdf/ec_declaration/a0030000007P7YREA0

RoHS/RoHS2

Declaration https://www.globtek.com/pdf/rohs_cert/a0030000007P7YREA0

REACH

Declaration https://www.globtek.com/pdf/iso_certificates/REACH.pdf

Conflict

Minerals <https://www.globtek.com/pdf/conflict-minerals.pdf>

Declaration

Delivering leading edge, innovative power solutions for more than **30** years....

Model:GT-21089-W

June 24, 2019

Model Parameters

Type	Wall Plug-in
Technology	Regulated Switchmode AC-DC Power Supply AC Adaptor
Category	ITE Power Supply
Input Voltage	100-240V~, 50-60 Hz
I/P Amps (A)	
Wattage (W)	19.0
Vout Range (V)	3.3-48
Efficiency Level	
Ingress Protection	
Size (mm)	74*49*40.5

Delivering leading edge, innovative power solutions for more than **30** years....

Model:GT-21089-W

June 24, 2019

ENCLOSURE

Delivering leading edge, innovative power solutions for more than **30** years....

Model:GT-21089-W

June 24, 2019

RATING TABLE

Model Number Voltage Amps(A) Watts(W) RFQ

Delivering leading edge, innovative power solutions for more than **30** years....

Model:GT-21089-W

June 24, 2019

SPECIFICATIONS

Delivering leading edge, innovative power solutions for more than **30** years....

Model:GT-21089-W

June 24, 2019

DERATING CURVE

Delivering leading edge, innovative power solutions for more than **30** years....

Model:GT-21089-W

June 24, 2019

Input Configuration

Delivering leading edge, innovative power solutions for more than 30 years....

Model:GT-21089-W

June 24, 2019

Output Configuration

Common output connector options:



L Type (Coaxial 5.5x2.5mm plug)



C Type (Coaxial 5.5x2.1mm plug)



K Type (Coaxial 3.5x1.3mm plug)



LL Type (5.5x2.5mm Locking 760k type)



CL Type (5.5x2.1mm Locking S761k type)



ML2 Type (Molex housing 43025-0200)



YL3 Type (KPPX-3P)



YL4 Type (KPPX-4P)



EJ1/2/3/4/5 (EIAJ RC-5320A type connectors)



MSB Type (Micro USB)



USBC Type (USB Type C)



Inquire for custom design

For a comprehensive list of options, [click here](#)

Contact GlobTek for your specific requirements or custom solutions.

Delivering leading edge, innovative power solutions for more than **30** years....

Model:GT-21089-W

June 24, 2019

Approvals

Logo